

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES LETTERS PATENT

TITLE: MULTIPLE BORE CHRISTMAS TREE OUTLET


INVENTOR(S): Gavin J. McIntosh
6 York Place, Top Flat
Edinburgh EH11 3AT
Scotland
A citizen of the United Kingdom

ATTORNEYS: Henry C. Query, Jr.
504 S. Pierce Ave.
Wheaton, IL 60187
(630) 260-8093

Certificate of Mailing (37 CFR 1.10)

"Express Mail" mailing label number ET682414334US.

I hereby certify that this application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to the Assistant Commissioner for Patents, Washington, DC 20231 on August 17, 2001.


Henry C. Query, Jr.

Multiple Bore Christmas Tree Outlet

Background of the Invention

This invention relates to production outlets for large bore Christmas trees.

Traditionally, buoyant oil markets have provided the financial justification
5 for the development of, and production from, multiple wells. However, current
market circumstances dictate that whilst production volume must be maintained,
it must be done with a reduced number of wells. This has led to the development
of larger bore production xmas trees.

Large bore production xmas trees, particularly subsea trees utilizing
10 horizontal outlets, present problems with outlet diameters. Current outlet valve
technology accommodates outlets of up to 7" (178 mm) diameter. Any
production outlet with a diameter of over 7" (178 mm) will require the
development of a new subsea gate valve, with the consequent costs involved, as
well as the disadvantages of increased size and weight of the new design.

Summary of the Invention

The present invention solves the above problems by enabling the use of
existing standard sized outlet valves and actuators in a large bore production
tree. To that end, the present invention provides a production Christmas tree
having multiple production outlets extending from a single production bore.
20 Splitting one large production outlet into two or more smaller outlets allows the
use of existing subsea gate valves and actuators, with each production outlet
being controlled by a separate, standard sized valve, thereby avoiding the cost of
development of a new larger subsea gate valve. This system has the further

benefit that pressure drops due to reservoir depletion, and associated flow assurance problems, can be alleviated by closing one of the production outlets. Erosion problems are also reduced. Preferably each production outlet has a different diameter. By selecting different outlets or combinations of outlets, a wide range of production flow rates can be catered for, as the reservoir pressure drops over the lifecycle of the field. In a preferred embodiment, two outlets are provided. These may be for example a 7" (178 mm) and a 5" (127 mm) outlet. However other diameters may be used, for example to suit smaller sized valves.

An illustrative embodiment of the invention is described below with reference to the drawings.

Brief Description of the Drawings

Fig. 1 schematically shows the vertical bore and single horizontal production outlet of a prior art large bore horizontal production tree; and

Fig. 2 schematically shows a dual production outlet horizontal tree embodying the invention.

Detailed Description of the Preferred Embodiments

The prior art horizontal xmas tree shown in Fig. 1 has a vertical through bore 10 and a single horizontal production outlet 12 branched off from the vertical bore 10. Annular seals 14, 16 surround the vertical bore 10 above and below the production outlet 12, to seal a tubing hanger (not shown) in the vertical bore 10, as is conventional. A gate valve 18 forming a production master valve is situated in the production outlet 12.

The embodiment of the invention shown in Fig. 2 is similar, except that the horizontal outlet 12 from the production bore is split into two separate outlets 20, 22. One of these outlets 20 is controlled by a 5" (127 mm) subsea gate valve 24 and actuator. The other outlet 22 is controlled by a 7" (178 mm) subsea gate valve 26 and actuator. Other multiple outlet configurations will be readily apparent, for example having other diameters to suit other anticipated production flow rates, or including three or more separate outlets, each controlled by an appropriately sized valve. Although gate valves are generally preferred, other forms of valve may be suitable in particular circumstances. The xmas tree of the invention may also incorporate other features known in prior xmas trees, for example an annulus and/or workover conduit, and a crossover conduit extending between the annulus/workover conduit and one or more of the production outlets. These additional conduits (shown in dotted lines in Fig. 2) will be controlled by suitable valves, as is conventional.

It should be recognized that, while the present invention has been described in relation to the preferred embodiments thereof, those skilled in the art may develop a wide variation of structural and operational details without departing from the principles of the invention. Therefore, the appended claims are to be construed to cover all equivalents falling within the true scope and spirit of the invention.